





MS-3D-RM

Specification

Model	MS-3D-RM	
Voltage	100~240V, 50/60Hz	
Power	4W	
Setting time	1-999min/0-999s	
Speed	10-40rpm	
Operation angle	20-99°	
Working Mode	Continuous/Timed	
Movement Mode	Rotation, Shaking, Angle	
Application tube	50mL	4 wells
(single piece)	7/10/15mL	5 wells
	5mL	8 wells
	1.5/2mL	24 wells
	0.5mL	11 wells
Machine size	Approx. 240 x 140 x 210mm	
Weight	Approx. 850g	
Certification	CE	

Opional Accessory







For 0.5 / 50ml tube

For 5 / 7 / 10 / 15ml tube

For 1.5 / 2ml tube

3 different type of tube frames (tube clamps)

Ordering Info

Cat. No.	Product Description	
MS-3D-RM-UK	3D Rotating Mixer with Adjustable Speed,UK	
MS-3D-RM-EU	3D Rotating Mixer with Adjustable Speed, EU	
MS-3D-RM-AU	3D Rotating Mixer with Adjustable Speed, AU	
MS-3D-RM-US	3D Rotating Mixer with Adjustable Speed, US	

- * All images are for reference only, actual products might differ from the pictures above.
- * Technical specifications subject to change without notice.
- *The tube frame can be different type on the two sides of the cross bar only on the both have same loading. Make sure the samples are in as balanced a position as possible. Please be aware that unbalanced force may cause damage to the machine.

Cat. No.	Product Description	
MS-3D-RM-001	O-RING, OD14xID7.8mm, MS-3D-RM	

Innovative Life Sciences Tools

Taiwan Office

No. 156, Sec. 1, Guoji Rd., Taoyuan Dist., Taoyuan City 330041, Taiwan T/+886-3-3762878 F/+886-3-3761310

Shanghai Office

Room 612, International business exhibition center, 9300 Hunan Road, Pudong, Shanghai, China National toll-free No.:400-823-9177 T/ +86-21-50795277 F/ +86-21-50795277

US Office

19959 Sea Gull Way Saratoga, CA 95070 U.S.A. T/ +1-408-366-9866 F/ +1-408-446-1107

India Office

D.No.7-143, 2nd Floor, St.No.2, Nagendra Nagar, Habsiguda, Hyderabad-500007. India T/ +91-40-27001515 T/ +91-40-27001586

*Could be compatibled with MO-MINI.

